MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0563 OSCILLATING EDGE SANDER 2 HP

Product Dimensions:

Weight..... 396 lbs.
Length/Width/Height..... 50-1/2 x 23 x 49 in.
Foot Print (Length/Width)..... 22-1/2 x 19-1/2 in.

Shipping Dimensions:

Type..... Not Available
Content..... Not Available
Weight..... N/A
Length/Width/Height..... N/A x N/A x N/A

Electrical:

Switch..... Magnetic Contactor and Overload Relay
Switch Voltage..... 220V
Cord Length..... 10 ft.
Cord Gauge..... 14 gauge
Minimum Circuit Size..... 15 amp
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 2 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Single
Amps..... 12A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer ..... Direct Drive
Bearings..... Shielded and Permanently Lubricated

Main Specifications:

Operation Information

Sanding Belt Speed..... 3150 FPM
Sanding Belt Oscillations..... 3/4 in.
Sanding Belt Length..... 89 in.
Sanding Belt Width..... 6 in.
Sanding Belt Tilt..... 0 - 90 deg.

The information contained herein is deemed accurate as of 10/7/2008 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.

Table Information

Table Length	26-7/8 in.
Table Width	12 in.
Table Thickness	1-1/4 in.
Table Travel	3-3/4 in.
Floor To Table Height	35-3/4 - 39-1/2 in.
End Table Length	11-1/2 in.
End Table Width	10 in.
End Table Thickness	3/4 in.
End Table Travel	10 in.

Platen Information

Platen Type	Steel with Graphite Pad
Platen Length	30-1/4 in.
Platen Width	6-3/4 in.
Platen Travel	0 - 90 deg.

Construction

Table Construction	Precision Ground Cast Iron
Frame Construction	Sheet Metal
Base Construction	Sheet Metal
Drive Roller Construction	Aluminum
Idler Roller Construction	Rubber
Paint	Powder Coated

Other Related Information

No Of Dust Ports	2
Dust Port Size	4 in.
Belt Release	Quick Release Lever
Drive Roller Size	7 in.
Idler Roller Size	3-7/8 in.

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	On the Base
Assembly Time	10 minutes
Sound Rating	90 dB

Features:

Sanding Surface Tilts Vertical to Horizontal
T-Slot Table and Miter Gauge
Quick Release Belt Tension Lever
Graphite Coated Platen
Oscillating Sanding Surfaces
Sanding Belt Oscillates at 52 Cycles per Minute
Includes 3 Spindles Drums: 1 1/2", 2", 3" x 4 1/2"
Platen Tilts 0 to 90 degrees (5 deg. Scale)

The information contained herein is deemed accurate as of 10/7/2008 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.